



# 福建省安源（安泰）橡胶科技有限公司

## EVA Depigmenting Agent AT-1213 技术使用说明书(TDS)

Active ingredients	EVA Depigmenting Agent	Other ingredients	——
--------------------	------------------------	-------------------	----

### Product introduction

This product is a new type of compound additive developed mainly for the production of scattered color and efflorescence in EVA foam. This product can improve the dispersion of the material, improve the coloring power and stability of the color material, and effectively solve the problem of EVA products, so as to improve the aesthetics of the product. This product is suitable for EVA foaming materials, including primary injection, secondary MD, large foam sheet. At the same time, this product also improves the brightness and vividness of the product and the stability of the color.
-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

### Product index

Items	appearance	density (20℃)	content	ash content	Mooney
Unit	White powder	g/cm <sup>3</sup>	%	%	ML(1+4)50℃
Index	——	1.15	≥90	≤5	≤0.5

### Usage method

Directly added to the original formula, without changing the structure of the formula
Suggested dosage: 1.5phr-2.0phr, Please increase or decrease according to the foaming ratio and actual requirements.

### Package specification/ shelf life

12.5kg/ bag
Twelve months from the date of production. If the storage is expired, it can still be used after re inspection

### Attention points

1. Light colors may be slightly different, need to do fine-tuning, but after fine-tuning the color is very stable	Flammability  <b>flammable</b>
2. Keep away from strong acids and alkali and non-polar oils	
3. Store in a well ventilated and dry place	

公司名称	福建省安源橡胶科技有限公司		
地址	福建省石狮市蚶江镇洪窟九龙山工业区22号		
电话	<a href="tel:0595-85151198">0595-85151198</a>	网址	<a href="http://www.fjayxj.com">www.fjayxj.com</a>